

STAIN-PROOF™

PREMIUM COUNTERTOP SEALER **PLUS**

STAIN-PROOF Plus™ is an impregnating, invisible and breathable sealer that protects natural stone countertops from damage caused by water, salts and oil-based stains. Treated countertop surfaces become easier to clean, maintain, and keep looking good for longer. STAIN-PROOF Plus™ provides lasting protection for natural stone that comes with a 25 year warranty*.



TYPICAL APPLICATIONS

STAIN-PROOF Plus™ is suitable for natural stone and concrete countertops.

BENEFITS

- The next generation of Dry-Treat™'s world leading STAIN-PROOF™ Original sealer, optimized for dense natural stone
- Permanent premium oil and water repellence. 25-year written performance warranty when applied by a Dry-Treat™ Accredited Applicator
- Three different custom sealing molecules for 3 levels of penetration and maximum stain repellence
- Includes a super penetrator for deep penetration of dense granites and marbles.
- Retains natural surface color and finish
- Super breathable: water vapor escapes freely preventing harmful moisture build-up inside the treated material
- Suitable for indoor, outdoor, residential and commercial use.

PACK SIZE

16 fl. oz. (1 pint / 473mL)

CAUTION:

Highly flammable liquid and vapour. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. Use only outdoors or in a well-ventilated area. Ground/bond container and receiving equipment. IN CASE OF FIRE, use alcohol resistant foam or normal protein foam for extinction. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

FIRST AID:

FIRST AID: IF INGESTED do NOT induce vomiting. IF INHALED, remove from contaminated area. Lay patient down. Keep warm and rested. IF YOU FEEL UNWELL call a POISON CENTER and seek immediate medical attention. IF IN CONTACT WITH SKIN, immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water and soap if available. IF IN EYES, wash out immediately with fresh running water. Remove contact lenses if easy to do so. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. Continue rinsing and seek immediate medical attention.

STORAGE

Keep container tightly sealed in a cool, well ventilated place. It is recommended that this product is best used within seven days of opening to avoid possible spoilage.

ACTIVE CONTENT

Over 60% active contents in alcohol.

VOC CONTENT

VOC compliant in containers having capacities of one Liter or less.

WARRANTY

*A 25-YEAR PERFORMANCE WARRANTY is offered when product applied by an Accredited Applicator following our written instructions and surface is maintained regularly using our written maintenance system, as outlined in our warranty document. Spills should still be cleaned up immediately to minimise absorption.



HOW TO USE

- 1. TEST PRODUCT ON A SMALL, INCONSPICUOUS AREA FIRST. Allow a 24-hour cure time to determine the ease of application and desired results**
2. Surface must be dry, clean and free of residues.
3. DO NOT thin product
4. Generously apply STAIN-PROOF™ using low pressure hand sprayer, clean brush or lamb wool applicator. Porous surfaces should have a mirror like 'wet' look for 3-5 seconds. Avoid contact with surrounding areas.
5. Wait for approximately 10 minutes but before the surface dries, then repeat step 4.
6. After the final coat, wait approximately 10 minutes but before the surface dries, then polish the surface thoroughly with clean, dry, white cloths, towels or similar to remove excess product, moistening cloth with STAIN-PROOF™ to ease polishing.
7. Use an organic solvent e.g. methylated spirits to clean equipment

NOTE: Sealer will not prevent surface etching, scuff marks or wear and may lighten or darken some surfaces. STAIN-PROOF Original™ will make the maintenance and cleaning of a treated surface much easier. Once cured, this product is food contact safe. Spills should be cleaned up immediately to minimize absorption.

PRECAUTIONS

Do not take internally. Apply when surface temperature is between 5 - 35°C (40 - 95°F). Avoid moisture contact with the surface for six hours after application. Surface may be used after 24 hours with full cure up to 4 weeks. Protect surrounding areas from over-spray. Keep away from drains, plants, water and soil. Do not empty into drains. Use only in well ventilated areas. Use a positive pressure respirator if ventilation is inadequate. Wear suitable solvent resistant gloves, protective clothing, safety goggles and an organic vapor respirator during application. Wash hands thoroughly after applying.

APPLICATION RATE

Surface Type	sq ft/ quart	sqm/ quart
Basalt - Dense (European)	120	12
Bluestone (Australian Basalt)	100	10
Poured Concrete Dense	70	7
Granite Flamed	60	6
Granite Honed	80	8
Granite Polished	120	12
Marble Honed	100	10
Marble Polished	150	15
Quartzite	100	10
Slate	70	7