

# STAIN-PROOF™

## PREMIUM IMPREGNATING SEALER



World leading protection for natural stone, tile, paving and grout



- Premium stain protection\*\*
- Protects against efflorescence, freeze-thaw and salt damage (Highly porous materials require Dry-Treat 40SK for freeze-thaw/salt protection)
- Breathable: water vapor permeates freely, avoiding moisture build-up inside the material
- Treated surfaces are easier to clean
- Retains wet slip resistance, existing color and finish
- Suitable for indoor, outdoor, residential and commercial use
- Provides long lasting protection and comes with 15 year warranty\*

### STAIN-PROOF™ will protect:

- |                   |                    |
|-------------------|--------------------|
| ■ Basalt          | ■ Marble           |
| ■ Brick           | ■ Quarry tiles     |
| ■ Cement pavers   | ■ Saltillo tiles   |
| ■ Clay pavers     | ■ Sandstone        |
| ■ Concrete        | ■ Slate            |
| ■ Encaustic tiles | ■ Terracotta tiles |
| ■ Granite         | ■ Terrazzo         |
| ■ Grout           | ■ Travertine       |
| ■ Limestone       |                    |



# BASIC SEALING GUIDE

## BEFORE SEALING:

- Surfaces must be thoroughly clean and dry before applying a sealer. Once sealed, the surface becomes water repellent, making it tough to remove existing stains.

## ALL YOU WILL NEED:

- STAIN-PROOF™
- Low pressure hand spray/lamb's wool applicator/brush
- Sufficient white absorbent cloths/towels
- Safety gear (gloves, protective eyewear, mask or chemical respirator if in a confined space)

## SEALING IN 5 EASY STEPS: (Refer to the back of the bottle for more information)



**1. TEST:** Test product on a small area of the surface, wait 24 hours, and ensure you are satisfied with the results.



**2. CLEAN:** Make sure the area to be treated is clean, dry and free of residues or topical coatings.



**3. FIRST COAT:** Generously saturate the surface with STAIN-PROOF™ using a lamb's wool applicator / brush / pump spray. Leave to penetrate for at least 10 minutes.



**4. SECOND COAT:** Before the first coat dries, apply a second generous coat of STAIN-PROOF™. Leave to penetrate again for at least 10 minutes.



**5. REMOVE EXCESS:** Before the second coat dries, **thoroughly polish off** all residue with clean, dry white cloths / towels. If the residue has been left too long, moisten a cloth with STAIN-PROOF™ to ease removal and polish off with dry cloths / towels.

*Note: Surface can be walked on 2-3 hours after application. Do not get the surface wet for at least 8-10 hrs.*

## MAINTAINING YOUR SEALED SURFACE:

Dry-Treat has developed specialist cleaners under the HANAFINN™ brand to clean and maintain your natural stone surface.



**HANAFINN  
Oxy-Klenza™**  
for outdoor surfaces  
and stain removal



**HANAFINN  
Rejuvenata™ Active**  
for indoor surfaces  
and stain removal



**HANAFINN  
Rejuvenata™ Spray**  
for daily  
countertop cleaning



**HANAFINN  
Eff-Erayza™**  
for removing of efflorescence,  
rust marks and grout haze

\*Warranty valid after being applied by an Accredited Applicator – see product label for details. Impregnating sealers do not protect against acid etching, wear, and water pressure. \*\*In accordance with ISO 10545-14 Determination of resistance to stains Class 5 (highest class)